DELAWARE COUNTY 1092 BETHEL ROAD GARNET VALLEY, PA 19060



Phone: (610) 459-1529 Fax: (610) 459-2921 www.betheltwp.com

Code Enforcement Office

CERTIFICATE OF OCCUPANCY APPLICATION

		No	
Name of Buyer:	Phone Number:		
Address:	City	v:	State & Zip:
Applicant/Agent:(if applicable)	Phone Number:		
Hereby applies for Certificate	of Occupancy for the following	property:	
Address:	City	v:	State & Zip:
Type of Occupancy:	☐ New Construction	☐ Re-Sale	☐ Commercial
Name of Seller/Owner:	Phone Number:		
Address:	City	r:	State & Zip:
Are there any special stipulation	ons/conditions pertaining to this	property:	es 🗆 No
If yes, please explain:			
Date of Settlement:	Email:		
	REQUIRES 48 HO	OUR NOTICE	
Return completed form to	the Code Enforcement Office	with the applicable f	ee in person, by email, or by fax:
	1092 Bethel Road, Garr	net Valley, PA 19060	
Email: code.secretary@betheltwp.com Fax: (610) 459-2921			
	Tax. (010) 4	33-2321	
Applicant Signature:		Dat	e:

DELAWARE COUNTY 1092 BETHEL ROAD GARNET VALLEY, PA 19060



Phone: (610) 459-1529 Fax: (610) 459-2921 www.betheltwp.com

RECOMMENDED RESALE RESIDENTIAL CHECKLIST FOR CERTIFICATE OF OCCUPANCY

Items to be inspected:

- 1. Smoke and CO detectors on every level including basement <u>AND</u> one smoke detector in every bedroom. Either battery operated or hard wired mounted on ceilings, but not in the rooms' corners. Smoke/CO detector in bedroom hallway cannot exceed twenty (20) feet. CO detectors shall not be plug-in.
- 2. Handrails on all steps that have four (4) or more risers.
- 3. Guardrail systems must be on all landings, porches, decks, or balconies which are over 30" above grade. Guardrail height must be 34"-38" above stair nosing with balusters no greater than 4" spacing.
- 4. Basements steps must be <u>enclosed on both sides</u> by either a guardrail system or wall and must have a continuous handrail that meets the dimensions in item #3.
- 5. Ground fault interrupter outlets (GFCI) to meet all requirements of the current International Electrical Code locations: Kitchen, Bathrooms, Garage, Basement, Exterior of the Home, Sump Pumps, and Washing Machines.
- 6. Pressure relief valve piping must be no more than 6" above the floor on hot water heaters or boilers. Pipe must be metallic or stamped "ASME 112.4.1" (Standard).
- 7. Sump pumps cannot be connected to the sewer system and must drain to the exterior of the building. Pumps must have check valve on discharge pipe.
- 8. House numbers must be of reflecting numbers on a contrasting background and be at least four (4) inches in height and have a ½ inch stroke.
- 9. Ingress and egress into the house. Must have one (1) all weather walkway surface and not have any trip surfaces and maintained in good condition. Steps must be no higher than 8 ¼".
- 10. Thumb turn deadbolt locks in lieu of keyed deadbolts.
- 11. Sidewalks to conform to Ordinance No. 115.
- 12. No chains or other devices limiting exit out of the house.
- 13. Freestanding kitchen ranges shall have an anti-tip device installed as required by all appliance manufacturers (IRC M1901.2).
- 14. Dryer exhaust ducts must have rigid pipe constructed of galvanized steel or aluminum.
- 15. Electrical wiring secured.
- 16. Electrical panel must be marked to indicate the device or equipment where the power supply originates.
- 17. Covers on all light fixtures.
- 18. Fire Extinguisher located in kitchen UL Listed, Multipurpose.
- 19. Chimney caps must be installed sloped to the outside and provide a drip edge.
- 20. Any other items the Code Official deems necessary for fire and safety.